



AQUILA II

Lavov flood light from the family AQUILA II with a power of 240W and an optics 60° degrees . CCT 4000K. With a total lumen output of 38400lm and a luminous efficiency of 160lm/W.DALI driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

| | |
|------------------|-------------------------|
| Item code | 86.10018.5423.02 |
|------------------|-------------------------|

| | |
|---------------------|----------------|
| Product type | Outdoor |
|---------------------|----------------|

| | |
|-----------------|--------------------|
| Category | Floodlights |
|-----------------|--------------------|

| | |
|---------------|------------------|
| Family | AQUILA II |
|---------------|------------------|

| | |
|------------------|------------------|
| Subfamily | AQUILA II |
|------------------|------------------|

| | |
|-------------------|---|
| Pictograms |      |
|-------------------|---|

50
60 Hz220
240 V

850°

SDCM
3Driver
INCL.IP
66CRI
70IK
0850000h
L70B50

Product

| | |
|-----------------------|------------|
| Real power (W) | 240 |
|-----------------------|------------|

| | |
|--------------------------------|--------------|
| Real luminous flux (Lm) | 38400 |
|--------------------------------|--------------|

| | |
|-----------------------------------|------------|
| Luminous efficiency (Lm/W) | 160 |
|-----------------------------------|------------|

| | |
|-----------------------|------------|
| Beam angle (°) | 60° |
|-----------------------|------------|

| | |
|----------------------|----------------------|
| Life time (h) | 50000h L70B50 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 66 |
|-----------|-----------|

| | |
|------------------------------------|----------------|
| Electrical class insulation | Class I |
|------------------------------------|----------------|

| | |
|---------------|--------------|
| Colour | Black |
|---------------|--------------|

| | |
|------------------------------|------------|
| Control gear included | Yes |
|------------------------------|------------|

| | |
|---------------------|-------------|
| Control gear | DALI |
|---------------------|-------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|-------------|
| Type of LED | 2835 |
|--------------------|-------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 4000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<5 |
|----------------------------------|------------------|

| | |
|------------|------------|
| CRI | ≥70 |
|------------|------------|

| | |
|-----------|-----------|
| IK | 08 |
|-----------|-----------|

Scheme

