



AQUILA II

Lavov flood light from the family AQUILA II with a power of 240W and an optics 55x125°, tilt55 degrees . CCT 4000K. With a total lumen output of 38400lm and a luminous efficiency of 160lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

Item code	86.I0018.5451.02
------------------	-------------------------

Product type	Indoor
---------------------	---------------

Category	Industrial
-----------------	-------------------


Family	AQUILA II
---------------	------------------

Subfamily	AQUILA II
------------------	------------------

Pictograms	
-------------------	--



Scheme



Product

Real power (W)	240
-----------------------	------------

Real luminous flux (Lm)	38400
--------------------------------	--------------

Luminous efficiency (Lm/W)	160
-----------------------------------	------------

Beam angle (°)	55x125°, tilt55
-----------------------	------------------------

Life time (h)	50000h L70B50
----------------------	----------------------

IP	66
-----------	-----------

Electrical class insulation	Class I
------------------------------------	----------------

Colour	Black
---------------	--------------

Control gear included	Yes
------------------------------	------------

Control gear	ON-OFF
---------------------	---------------

Light source	LED
---------------------	------------

Type of LED	2835
--------------------	-------------

Colour temperature (K)	4000
-------------------------------	-------------

Colour consistency (SDCM)	SDCM<5
----------------------------------	------------------

CRI	≥70
------------	------------

IK	08
-----------	-----------