## FLOODLIGHTS - AQUILA II





## AQUILA II

Lavov flood light from the family AQUILA II with a power of 240W and an optics 26x60° tilt10° degrees . CCT 4000K. With a total lumen output of 38400lm and a luminous efficiency of 160lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

| ltem code    | 86.10018.5461.02                   |
|--------------|------------------------------------|
| Product type | Indoor                             |
| Category     | Floodlights                        |
| Family       | AQUILA II                          |
| Subfamily    | AQUILA II                          |
| Pictograms   | (☐) 50 Hz 220 V 50 SDCM 3          |
|              | CE Driver On Off                   |
|              | IP CRI IK 50000h   66 70 08 L70B50 |

| Product                     |                |
|-----------------------------|----------------|
| Real power (W)              | 240            |
| Real luminous flux (Lm)     | 38400          |
| Luminous efficiency (Lm/W)  | 160            |
| Beam angle (º)              | 26x60° tilt10° |
| Life time (h)               | 50000h L70B50  |
| IP                          | 66             |
| Electrical class insulation | Class I        |
| Colour                      | Black          |
| Control gear included       | Yes            |
| Control gear                | ON-OFF         |
| Light source                | LED            |
| Type of LED                 | 2835           |
| Colour temperature (K)      | 4000           |
| Colour consistency (SDCM)   | SDCM<5         |
| CRI                         | ≥70            |
| IK                          | 08             |

## Scheme

