



AQUILA II

Lavov flood light from the family AQUILA II with a power of 240W and an optics 26x60° tilt10° degrees . CCT 4000K. With a total lumen output of 38400lm and a luminous efficiency of 160lm/W.DALI driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

Item code	86.I0018.5463.02
Product type	Outdoor
Category	Floodlights
Family	AQUILA II
Pictograms	<div><div></div><div>50 60 Hz</div><div>220 240 V</div><div></div><div>850°</div><div>SDCM 3</div></div> <div><div></div><div>Driver INCL.</div><div></div><div></div><div></div></div> <div><div>IP 66</div><div>CRI 70</div><div>IK 08</div><div>50000h L70B50</div></div>

Scheme



Product	
Real power (W)	240
Real luminous flux (Lm)	38400
Luminous efficiency (Lm/W)	160
Beam angle (°)	26x60° tilt10°
Life time (h)	50000h L70B50
IP	66
Electrical class insulation	Class I
Colour	Black
Control gear included	Yes
Control gear	DALI
Light source	LED
Type of LED	2835
Colour temperature (K)	4000
Colour consistency (SDCM)	SDCM<5
CRI	≥70
IK	08