


















AQUILA II

Lavov flood light from the family AQUILA II with a power of 300W and an optics 26x60° tilt10° degrees . CCT 4000K. With a total lumen output of 48000lm and a luminous efficiency of 160lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

|              |   |
|--------------|---|
| Item code    | 86.I0018.6461.02  |
| Product type | Outdoor   |
| Category     | Floodlights   |
| Family       | AQUILA II   |
| Pictograms   |     <br>    <br>    |

Scheme



|                             |                |
|-----------------------------|----------------|
| Product                     |                |
| Real power (W)              | 300            |
| Real luminous flux (Lm)     | 48000          |
| Luminous efficiency (Lm/W)  | 160            |
| Beam angle (°)              | 26x60° tilt10° |
| Life time (h)               | 50000h L70B50  |
| IP                          | 66             |
| Electrical class insulation | Class I        |
| Colour                      | Black          |
| Control gear included       | Yes            |
| Control gear                | ON-OFF         |
| Light source                | LED            |
| Type of LED                 | 2835           |
| Colour temperature (K)      | 4000           |
| Colour consistency (SDCM)   | SDCM<5         |
| CRI                         | ≥70            |
| IK                          | 08             |