

## OVNI-R

Lavov Highbay from the family OVNI-R with a power of 90W and a 60 degrees beam angle. Surface mounted. With a total lumen output of 9000lm and a luminous efficiency of 100lm/W. Driver ON-OFF .Made in Die cast aluminium and glass refractor . Class II issolation. IP65 and IK09 . Mains voltage 120-277V . UGR19. Finished in black colour. CCT 4000K.

| | |
|---|---|
| **Item code** | **86.I035.1431.02** |
| **Product type** | **Indoor** |
| **Category** | **Industrial** |
| **Family** | **OVNI** |
| **Subfamily** | **OVNI-R** |
| **Pictograms** | CRI 80 · CE · Driver INCL. · On Off · 1-10V |

| **Dimensions** | |
|---|---|
| **Product dimensions (mm)** | **ø358*55mm** |

| **Product** | |
|---|---|
| **Real power (W)** | **90** |
| **Real luminous flux (Lm)** | **9000** |
| **Luminous efficiency (Lm/W)** | **100** |
| **Beam angle (º)** | **60** |
| **IP** | **65** |
| **Electrical class insulation** | **Class II** |
| **Electrical feeding** | **120-277V** |
| **Colour** | **black** |
| **U. G. R** | **19** |
| **Control gear included** | **yes** |
| **Control gear** | **ON-OFF** |
| **Light source** | **LED** |
| **Type of LED** | **sanan** |
| **Colour temperature (K)** | **4000** |
| **IK** | **09** |