



SLINE

Lavov linear system from the family SLINE with a power of $40\mathrm{W}$ and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 4000lm and an efficacy of 100 lm/W . Made in Extruded Aluminium and finished in Black color. ON-OFF driver.

| Item code | 86.L001.2301.02 Indoor Linear Systems SLINE | | | |
|--------------------------|---|--|--|--|
| Product type Category | | | | |
| | | | | |
| Pictograms | | | | |
| | On IP 50000h L80B10 | | | |

| Product | | |
|----------------------------|---------------|--|
| Real power (W) | 40 | |
| Real luminous flux (Lm) | 4000 | |
| Luminous efficiency (Lm/W) | 100 | |
| Beam angle (º) | 110 | |
| Life time (h) | 50000h L80B10 | |
| IP | 20 | |
| Colour | Black | |
| U. G. R | 22 | |
| Control gear included | Yes | |
| Control gear | ON-OFF | |
| Colour temperature (K) | 3000 | |
| Colour consistency (SDCM) | SDCM<3 | |
| CRI | 80 | |

| Product dimensions (mm) | |
|-------------------------|--|
| Dimensions | |

| 50 | 1200 | - |
|----|------|---|
| 75 | | |