

SLINE

Lavov linear system from the family SLINE with a power of 40W and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 4000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in Black color. 0-10V Dim driver.

| Item code | 86.L001.2402.02 |
|--------------|-------------------------------------|
| Product type | Indoor |
| Category | Linear Systems |
| Family | SLINE |
| Subfamily | SLINE |
| Pictograms | (1) 220 v CRI CC Driver INCL |
| | On IP 50000h Off 1-10V 20 L80B10 |


Dimensions

Product dimensions (mm) 50x75X1200mm

Scheme

1200 - 1200 - 1200

Photometry



| Product | |
|----------------------------|---------------|
| Real power (W) | 40 |
| Real luminous flux (Lm) | 4000 |
| Luminous efficiency (Lm/W) | 100 |
| Beam angle (º) | 110 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Colour | Black |
| U. G. R | 22 |
| Control gear included | Yes |
| Control gear | 0-10V Dim |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |