



SLINE

Lavov linear system from the family SLINE with a power of $40\mathrm{W}$ and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 4000lm and an efficacy of 100 lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

| Item code | 86.L001.2403.02 | | | |
|--------------|----------------------------------|--|--|--|
| Product type | Indoor | | | |
| Category | Linear Systems | | | |
| Family | SLINE | | | |
| Pictograms | 220 v CRI 80 C € Driver INCL. | | | |
| | On IP 50000h Off 1-10V 20 L80B10 | | | |

| Product | |
|----------------------------|---------------|
| Real power (W) | 40 |
| Real luminous flux (Lm) | 4000 |
| Luminous efficiency (Lm/W) | 100 |
| Beam angle (º) | 110 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Colour | Black |
| U. G. R | 22 |
| Control gear included | Yes |
| Control gear | DALI |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |

| Product dimensions (mm) | 50v75Y1200mm |
|-------------------------|--------------|
| Dimensions | |

| Scheme | | |
|----------|--|--|
| Julienie | | |
| | | |

| 50 | 1200 | - |
|----|------|---|
| 75 | | |