



**SLINE**

Lavov linear system from the family SLINE with a power of 40W and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 4000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

<b>Item code</b>	<b>86.L001.2403.02</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>SLINE</b>
<b>Subfamily</b>	<b>SLINE</b>


**Pictograms**



**Dimensions**

**Product dimensions (mm) 50x75X1200mm**

**Scheme**



**Product**

<b>Real power (W)</b>	<b>40</b>
<b>Real luminous flux (Lm)</b>	<b>4000</b>
<b>Luminous efficiency (Lm/W)</b>	<b>100</b>
<b>Beam angle (°)</b>	<b>110</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>20</b>
<b>Colour</b>	<b>Black</b>
<b>U. G. R</b>	<b>22</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>80</b>