



SLINE

Lavov linear system from the family SLINE with a power of 60W and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 6000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

Item code 86.L001.3303.02 Product type Indoor Category Linear Systems SLINE Family Pictograms ²²⁰ v 240 v **CRI** 80 Driver INCL. $(\underline{+})$ CE **IP** 20 50000h **L**80**B**10 1-10V

Dimensions

Product dimensions (mm)

50x75X1800mm

Scheme

| | 1. | | 1800 |) | |
|---|----|--|------|---|---|
| 1 | | | | | _ |
| 2 | | | | | |
| ļ | | | | | |

| Product | | | |
|----------------------------|---------------|--|--|
| Real power (W) | 60 | | |
| Real luminous flux (Lm) | 6000 100 | | |
| Luminous efficiency (Lm/W) | | | |
| Beam angle (º) | 110 | | |
| Life time (h) | 50000h L80B10 | | |
| IP | 20 | | |
| Colour | Black 22 | | |
| U. G. R | | | |
| Control gear included | Yes | | |
| Control gear | DALI | | |
| Colour temperature (K) | 3000 | | |
| Colour consistency (SDCM) | SDCM<3 | | |
| CRI | 80 | | |

