



SLINE

Lavov linear system from the family SLINE with a power of 60Wand an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 6000lm and an efficacy of 100 lm/W . Made in Extruded Aluminium and finished in White color. DALI driver.

| Item code | 86.L001.3403.01 | | | | |
|--------------|-----------------|---------------------------------|-----------|-----------------------------------|-----------------|
| Product type | Indoor | | | | |
| Category | Linear Systems | | | | |
| Family | SLINE | | | | |
| Pictograms | | ²²⁰ ₂₄₀ V | CRI 80 | C€ | Driver INCL. |
| | On Off | 1-10V | IP 20 | 50000h L 80 B 10 | |

| Product | | | |
|----------------------------|---------------|--|--|
| Real power (W) | 60 | | |
| Real luminous flux (Lm) | 6000 | | |
| Luminous efficiency (Lm/W) | 100 | | |
| Beam angle (º) | 110 | | |
| Life time (h) | 50000h L80B10 | | |
| IP | 20 | | |
| Colour | White | | |
| U. G. R | 22 | | |
| Control gear included | Yes | | |
| Control gear | DALI | | |
| Colour temperature (K) | 4000 | | |
| Colour consistency (SDCM) | SDCM<3 | | |
| CRI | 80 | | |

| Dimensions | |
|-------------------------|--------------|
| Product dimensions (mm) | 50v75¥1800mm |

| Scheme | | |
|--------|--|--|
| | | |

| 50 | 1800 |
|----|------|
| 75 | |