



SLINE

Lavov linear system from the family SLINE with a power of $80\mbox{W}$ and an optics 77 degrees beam angle. CCT 3000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 7200lm and an efficacy of 90 lm/W . Made in Extruded Aluminium and finished in Black color. ON-OFF driver.

| Item code | 86.L001.4391.02 Indoor Linear Systems SLINE | | | |
|--------------|---|--|--|--|
| Product type | | | | |
| Category | | | | |
| Family | | | | |
| Pictograms | 220 v CRI C C Driver INCL. | | | |
| | On | | | |

| Product | | |
|----------------------------|---------------|--|
| Real power (W) | 80 | |
| Real luminous flux (Lm) | 7200 | |
| Luminous efficiency (Lm/W) | 90 | |
| Beam angle (º) | 77 | |
| Life time (h) | 50000h L80B10 | |
| IP | 20 | |
| Colour | Black | |
| U. G. R | <19 | |
| Control gear included | Yes | |
| Control gear | ON-OFF | |
| Colour temperature (K) | 3000 | |
| Colour consistency (SDCM) | SDCM<3 | |
| CRI | 80 | |

| Product dimensions (mm) | 50x75Y2400mm |
|-------------------------|--------------|
| Dimensions | |

Scheme

