



**SLINE**

Lavov linear system from the family SLINE with a power of 80W and an optics 77 degrees beam angle. CCT 4000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 7200lm and an efficacy of 90lm/W . Made in Extruded Aluminium and finished in White color. DALI driver.

**Dimensions**

**Product dimensions (mm)**      **50x75X2400mm**

**Scheme**



<b>Item code</b>	<b>86.L001.4493.01</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>SLINE</b>

**Pictograms**

	220 240 V	CRI 80	CE	Driver INCL.
On Off	1-10V	IP 20	50000h L80B10	

<b>Product</b>	
<b>Real power (W)</b>	<b>80</b>
<b>Real luminous flux (Lm)</b>	<b>7200</b>
<b>Luminous efficiency (Lm/W)</b>	<b>90</b>
<b>Beam angle (°)</b>	<b>77</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>20</b>
<b>Colour</b>	<b>White</b>
<b>U. G. R</b>	<b>19</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM3</b>
<b>CRI</b>	<b>80</b>