

## MLINE

Lavov linear system from the family MLINE with a power of 20W and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 2000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

<b>Item code</b>	<b>86.L002.1303.02</b>
------------------	------------------------

<b>Product type</b>	<b>Indoor</b>
---------------------	---------------

<b>Category</b>	<b>Linear Systems</b>
-----------------	-----------------------

<b>Family</b>	<b>MLINE</b>
---------------	--------------

<b>Pictograms</b>	    
	   

220  
240 VCRI  
80Driver  
INCLOn  
Off


1-10V

IP  
2050000h  
L80B10

## Dimensions

<b>Product dimensions (mm)</b>	<b>75x75X600mm</b>
--------------------------------	--------------------

## Scheme



## Product

<b>Real power (W)</b>	<b>20</b>
-----------------------	-----------

<b>Real luminous flux (Lm)</b>	<b>2000</b>
--------------------------------	-------------

<b>Luminous efficiency (Lm/W)</b>	<b>100</b>
-----------------------------------	------------

<b>Beam angle (°)</b>	<b>110</b>
-----------------------	------------

<b>Life time (h)</b>	<b>50000h L80B10</b>
----------------------	----------------------

<b>IP</b>	<b>20</b>
-----------	-----------

<b>Colour</b>	<b>Black</b>
---------------	--------------

<b>U. G. R</b>	<b>22</b>
----------------	-----------

<b>Control gear included</b>	<b>Yes</b>
------------------------------	------------

<b>Control gear</b>	<b>DALI</b>
---------------------	-------------

<b>Colour temperature (K)</b>	<b>3000</b>
-------------------------------	-------------

<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
----------------------------------	------------------

<b>CRI</b>	<b>80</b>
------------	-----------