



MLINE

Lavov linear system from the family MLINE with a power of 20W and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 2000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in White color. ON-OFF driver.

Item code	86.L002.1401.01
------------------	------------------------

Product type	Indoor
---------------------	---------------

Category	Linear Systems
-----------------	-----------------------

Family	MLINE
---------------	--------------

Pictograms	    
	   

220
240 VCRI
80Driver
INCL.On
Off


1-10V

IP
2050000h
L80B10

Dimensions

Product dimensions (mm)	75x75X600mm
--------------------------------	--------------------

Scheme



Product

Real power (W)	20
-----------------------	-----------

Real luminous flux (Lm)	2000
--------------------------------	-------------

Luminous efficiency (Lm/W)	100
-----------------------------------	------------

Beam angle (°)	110
-----------------------	------------

Life time (h)	50000h L80B10
----------------------	----------------------

IP	20
-----------	-----------

Colour	White
---------------	--------------

U. G. R	22
----------------	-----------

Control gear included	Yes
------------------------------	------------

Control gear	ON-OFF
---------------------	---------------

Colour temperature (K)	4000
-------------------------------	-------------

Colour consistency (SDCM)	SDCM<3
----------------------------------	------------------

CRI	80
------------	-----------