



MLINE

Lavov linear system from the family MLINE with a power of 20W $\,$ and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 2000lm and an efficacy of 100 lm/W . Made in Extruded Aluminium and finished in Black color. ON-OFF driver.

| Dimensions | |
|-------------------------|-------------|
| Product dimensions (mm) | 75x75X600mm |

| Item code | 86.L002.1401.02 | | | |
|--------------|----------------------------------|--|--|--|
| Product type | Indoor | | | |
| Category | Linear Systems MLINE | | | |
| Family | | | | |
| Subfamily | MLINE | | | |
| Pictograms | 220 v CRI C C Driver INCL. | | | |
| | On IP 50000h Off 1-10V 20 L80B10 | | | |

| 75 | 1 | 600 |
|----|----|-----|
| | П | |
| | 75 | |

| Product | | |
|----------------------------|---------------|--|
| Real power (W) | 20 | |
| Real luminous flux (Lm) | 2000 | |
| Luminous efficiency (Lm/W) | 100 | |
| Beam angle (º) | 110 | |
| Life time (h) | 50000h L80B10 | |
| IP | 20 | |
| Colour | Black | |
| U. G. R | 22 | |
| Control gear included | Yes | |
| Control gear | ON-OFF | |
| Colour temperature (K) | 4000 | |
| Colour consistency (SDCM) | SDCM<3 | |
| CRI | 80 | |

Scheme