



**MLINE**

Lavov linear system from the family MLINE with a power of 20W and a beam angle of 120°. Finished in Black colour. Dimensions 75x75X600mm. With a total lumen output of 2000lm and a luminous efficacy of 100lm/W. Made in Extruded Aluminium. Driver DALI. CCT 4000K.

**Dimensions**

**Product dimensions (mm)**      **75x75X600mm**

**Scheme**



**Photometry**



<b>Item code</b>	<b>86.L002.1403.02</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>MLINE</b>
<b>Subfamily</b>	<b>MLINE</b>

**Pictograms**

- 220 240 V
- CRI 80
- CE
- Driver INCL.
- On Off
- 1-10V
- IP 20
- 50000h L80B10

<b>Product</b>	
<b>Real power (W)</b>	<b>20</b>
<b>Real luminous flux (Lm)</b>	<b>2000</b>
<b>Luminous efficiency (Lm/W)</b>	<b>100</b>
<b>Beam angle (°)</b>	<b>120</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>20</b>
<b>Colour</b>	<b>Black</b>
<b>U. G. R</b>	<b>19</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM3</b>
<b>CRI</b>	<b>80</b>