

MLINE

Lavov linear system from the family MLINE with a power of 20W and an optics 77 degrees beam angle. CCT 4000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 1800lm and an efficacy of 90lm/W . Made in Extruded Aluminium and finished in White color. ON-OFF driver.



| | |
|--------------|--|
| Item code | 86.L002.1491.01 |
| Product type | Indoor |
| Category | Linear Systems |
| Family | MLINE |
| Pictograms | <div><div></div><div>220 240 V</div><div>CRI 80</div><div>CE</div><div>Driver INCL.</div><div>On Off</div><div>1-10V</div><div>IP 20</div><div>50000h L80B10</div></div> |

| | |
|----------------------------|---------------|
| Product | |
| Real power (W) | 20 |
| Real luminous flux (Lm) | 1800 |
| Luminous efficiency (Lm/W) | 90 |
| Beam angle (º) | 77 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Colour | White |
| U. G. R | <19 |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |

Dimensions

Product dimensions (mm) 75x75X600mm

Scheme

