



MLINE

Lavov linear system from the family MLINE with a power of 40W and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 4000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in Black color. 0-10V Dim driver.

| | |
|------------------|------------------------|
| Item code | 86.L002.2302.02 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|-----------------------|
| Category | Linear Systems |
|-----------------|-----------------------|

| | |
|---------------|--------------|
| Family | MLINE |
|---------------|--------------|

| | |
|------------------|--------------|
| Subfamily | MLINE |
|------------------|--------------|


| | |
|-------------------|---|
| Pictograms |      |
| |     |



Dimensions

| | |
|--------------------------------|---------------------|
| Product dimensions (mm) | 75x75X1200mm |
|--------------------------------|---------------------|

Scheme



Product

| | |
|-----------------------|-----------|
| Real power (W) | 40 |
|-----------------------|-----------|

| | |
|--------------------------------|-------------|
| Real luminous flux (Lm) | 4000 |
|--------------------------------|-------------|

| | |
|-----------------------------------|------------|
| Luminous efficiency (Lm/W) | 100 |
|-----------------------------------|------------|

| | |
|-----------------------|------------|
| Beam angle (°) | 110 |
|-----------------------|------------|

| | |
|----------------------|----------------------|
| Life time (h) | 50000h L80B10 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 20 |
|-----------|-----------|

| | |
|---------------|--------------|
| Colour | Black |
|---------------|--------------|

| | |
|----------------|-----------|
| U. G. R | 22 |
|----------------|-----------|

| | |
|------------------------------|------------|
| Control gear included | Yes |
|------------------------------|------------|

| | |
|---------------------|------------------|
| Control gear | 0-10V Dim |
|---------------------|------------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 3000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 80 |
|------------|-----------|