



MLINE

Lavov linear system from the family MLINE with a power of $40\mbox{W}$ and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 4000lm and an efficacy of 100 lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

| Item code | 86.L002.2303.02 | | |
|--------------|-----------------------------|--|--|
| Product type | Indoor Linear Systems MLINE | | |
| Category | | | |
| Family | | | |
| Pictograms | 220 v CRI C € Driver INCL. | | |
| | On IP 50000h L80B10 | | |

| Product | | |
|----------------------------|---------------|--|
| Real power (W) | 40 | |
| Real luminous flux (Lm) | 4000 | |
| Luminous efficiency (Lm/W) | 100 | |
| Beam angle (º) | 110 | |
| Life time (h) | 50000h L80B10 | |
| IP | 20 | |
| Colour | Black | |
| U. G. R | 22 | |
| Control gear included | Yes | |
| Control gear | DALI | |
| Colour temperature (K) | 3000 | |
| Colour consistency (SDCM) | SDCM<3 | |
| CRI | 80 | |

| Dimensions |
|------------|
| |

Scheme

| 75 | 1200 | |
|----|------|--|
| | | |
| 15 | | |