


MLINE

Lavov linear system from the family MLINE with a power of 40W and an optics 77 degrees beam angle. CCT 3000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 3600lm and an efficacy of 90lm/W . Made in Extruded Aluminium and finished in Black color. 0-10V Dim driver.



| | |
|--------------|--|
| Item code | 86.L002.2392.02 |
| Product type | Indoor |
| Category | Linear Systems |
| Family | MLINE |
| Subfamily | MLINE |
| Pictograms | <div><div></div><div>220 240 V</div><div>CRI 80</div><div>CE</div><div>Driver INCL.</div><div>On Off</div><div>1-10V</div><div>IP 20</div><div>50000h L80B10</div></div> |

| | |
|----------------------------|---------------|
| Product | |
| Real power (W) | 40 |
| Real luminous flux (Lm) | 3600 |
| Luminous efficiency (Lm/W) | 90 |
| Beam angle (°) | 77 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Colour | Black |
| U. G. R | <19 |
| Control gear included | Yes |
| Control gear | 0-10V Dim |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |

Dimensions

Product dimensions (mm) 75x75X1200mm

Scheme

