



MLINE

Lavov linear system from the family MLINE with a power of $40\mbox{W}$ and an optics 77 degrees beam angle. CCT 3000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 3600lm and an efficacy of 90 lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

| Item code | 86.L002.2393.02 Indoor Linear Systems | | |
|-----------------------|---------------------------------------|--|--|
| Product type Category | | | |
| | | | |
| Subfamily | MLINE | | |
| Pictograms | 220 v CRI C € Driver INCL. | | |
| | On IP 50000h L80B10 | | |

| Dimensions | |
|-------------------------|--------------|
| Product dimensions (mm) | 75x75X1200mm |

| Scheme | | | | |
|--------|---|------|----|--|
| 75 | - | 1200 | -1 | |

| Product | | | |
|----------------------------|---------------|--|--|
| Real power (W) | 40 | | |
| Real luminous flux (Lm) | 3600 | | |
| Luminous efficiency (Lm/W) | 90 | | |
| Beam angle (º) | 77 | | |
| Life time (h) | 50000h L80B10 | | |
| IP | 20 | | |
| Colour | Black | | |
| U. G. R | <19 | | |
| Control gear included | Yes | | |
| Control gear | DALI | | |
| Colour temperature (K) | 3000 | | |
| Colour consistency (SDCM) | SDCM<3 | | |
| CRI | 80 | | |