



MLINE

Lavov linear system from the family MLINE with a power of 40W and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 4000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

Item code	86.L002.2403.02
------------------	------------------------

Product type	Indoor
---------------------	---------------

Category	Linear Systems
-----------------	-----------------------

Family	MLINE
---------------	--------------

Pictograms	    
	   



Product

Real power (W)	40
-----------------------	-----------

Real luminous flux (Lm)	4000
--------------------------------	-------------

Luminous efficiency (Lm/W)	100
-----------------------------------	------------

Beam angle (°)	110
-----------------------	------------

Life time (h)	50000h L80B10
----------------------	----------------------

IP	20
-----------	-----------

Colour	Black
---------------	--------------

U. G. R	22
----------------	-----------

Control gear included	Yes
------------------------------	------------

Control gear	DALI
---------------------	-------------

Colour temperature (K)	4000
-------------------------------	-------------

Colour consistency (SDCM)	SDCM<3
----------------------------------	------------------

CRI	80
------------	-----------

Dimensions

Product dimensions (mm)	75x75X1200mm
--------------------------------	---------------------

Scheme

