



| Dimensions | |
|-------------------------|--------------|
| Product dimensions (mm) | 75x75X1750mm |

| Scheme | |
|--------|--|
| | |

MLINE

Lavov linear system from the family MLINE with a power of 60W and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 6000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in White color. ON-OFF driver.

| | | | | | |
|--------------|-----------------|--------------|-----------|------------------|-----------------|
| Item code | 86.L002.3301.01 | | | | |
| Product type | Indoor | | | | |
| Category | Linear Systems | | | | |
| Family | MLINE | | | | |
| Pictograms | | 220 240 V | CRI 80 | CE | Driver INCL. |
| | On Off | 1-10V | IP 20 | 50000h L80B10 | |

| Product | |
|----------------------------|---------------|
| Real power (W) | 60 |
| Real luminous flux (Lm) | 6000 |
| Luminous efficiency (Lm/W) | 100 |
| Beam angle (º) | 110 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Colour | White |
| U. G. R | 22 |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |