


MLINE


Lavov linear system from the family MLINE with a power of 60W and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 6000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in White color. DALI driver.



Dimensions

Product dimensions (mm) 75x75X1800mm

Scheme



|              |   |
|--------------|---|
| Item code    | 86.L002.3303.01   |
| Product type | Indoor  |
| Category     | Linear Systems  |
| Family       | MLINE   |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div>CRI<br/>80</div><div>CE</div><div>Driver<br/>INCL.</div><div>On<br/>Off</div><div><br/>1-10V</div><div>IP<br/>20</div><div>50000h<br/>L80B10</div></div> |

|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 60            |
| Real luminous flux (Lm)    | 6000          |
| Luminous efficiency (Lm/W) | 100           |
| Beam angle (º)             | 110           |
| Life time (h)              | 50000h L80B10 |
| IP                         | 20            |
| Colour                     | White         |
| U. G. R                    | 22            |
| Control gear included      | Yes           |
| Control gear               | DALI          |
| Colour temperature (K)     | 3000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |