



MLINE

Lavov linear system from the family MLINE with a power of $80\mbox{W}$ and an optics 77 degrees beam angle. CCT 3000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 7200lm and an efficacy of 90 lm/W . Made in Extruded Aluminium and finished in Black color. ON-OFF driver.

| Product type | 86.L | 86.L002.4391.02 | | | | |
|--------------|-----------|-----------------|-----------|---------------------------|-----------------|--|
| | Indo | Indoor | | | | |
| Category | Line | Linear Systems | | | | |
| Family | MLINE | | | | | |
| Pictograms | | 220 240 V | CRI 80 | c€ | Driver INCL. | |
| | On Off | 1-10V | IP 20 | 50000h L80 B 10 | | |

| ` | | | |
|----------------------------|---------------|--|--|
| Product | | | |
| Real power (W) | 80 | | |
| Real luminous flux (Lm) | 7200 | | |
| Luminous efficiency (Lm/W) | 90 | | |
| Beam angle (º) | 77 | | |
| Life time (h) | 50000h L80B10 | | |
| IP | 20 | | |
| Colour | Black | | |
| U. G. R | <19 | | |
| Control gear included | Yes | | |
| Control gear | ON-OFF | | |
| Colour temperature (K) | 3000 | | |
| Colour consistency (SDCM) | SDCM<3 | | |
| CRI | 80 | | |

| Dimensions | |
|-------------------------|--------------|
| Product dimensions (mm) | 75x75X2400mm |

| Scheme | | | |
|--------|--|--|--|
| | | | |

