



### MLINE

Lavov linear system from the family MLINE with a power of 80W and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 8000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in White color. ON-OFF driver.

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.L002.4401.01</b> |
|------------------|------------------------|

|                     |               |
|---------------------|---------------|
| <b>Product type</b> | <b>Indoor</b> |
|---------------------|---------------|

|                 |                       |
|-----------------|-----------------------|
| <b>Category</b> | <b>Linear Systems</b> |
|-----------------|-----------------------|

|               |              |
|---------------|--------------|
| <b>Family</b> | <b>MLINE</b> |
|---------------|--------------|

**Pictograms**



### Dimensions

|                                |                     |
|--------------------------------|---------------------|
| <b>Product dimensions (mm)</b> | <b>75x75X1800mm</b> |
|--------------------------------|---------------------|

### Scheme



### Product

|                       |           |
|-----------------------|-----------|
| <b>Real power (W)</b> | <b>80</b> |
|-----------------------|-----------|

|                                |             |
|--------------------------------|-------------|
| <b>Real luminous flux (Lm)</b> | <b>8000</b> |
|--------------------------------|-------------|

|                                   |            |
|-----------------------------------|------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>100</b> |
|-----------------------------------|------------|

|                       |            |
|-----------------------|------------|
| <b>Beam angle (°)</b> | <b>110</b> |
|-----------------------|------------|

|                      |                      |
|----------------------|----------------------|
| <b>Life time (h)</b> | <b>50000h L80B10</b> |
|----------------------|----------------------|

|           |           |
|-----------|-----------|
| <b>IP</b> | <b>20</b> |
|-----------|-----------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>White</b> |
|---------------|--------------|

|                |           |
|----------------|-----------|
| <b>U. G. R</b> | <b>22</b> |
|----------------|-----------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>Yes</b> |
|------------------------------|------------|

|                     |               |
|---------------------|---------------|
| <b>Control gear</b> | <b>ON-OFF</b> |
|---------------------|---------------|

|                               |             |
|-------------------------------|-------------|
| <b>Colour temperature (K)</b> | <b>4000</b> |
|-------------------------------|-------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;3</b> |
|----------------------------------|------------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>80</b> |
|------------|-----------|