

MLINE


Lavov linear system from the family MLINE with a power of 80W and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 8000lm and an efficacy of 100lm/W . Made in Extruded Aluminium and finished in White color. 0-10V Dim driver.



Dimensions

Product dimensions (mm) 75x75X2400mm

Scheme



| | |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item code | 86.L002.4402.01 |
| Product type | Indoor |
| Category | Linear Systems |
| Family | MLINE |
| Subfamily | MLINE |
| Pictograms | <div><div></div><div>220 240 V</div><div>CRI 80</div><div>CE</div><div>Driver INCL.</div><div>On Off</div><div>1-10V</div><div>IP 20</div><div>50000h L80B10</div></div> |

| | |
|----------------------------|---------------|
| Product | |
| Real power (W) | 80 |
| Real luminous flux (Lm) | 8000 |
| Luminous efficiency (Lm/W) | 100 |
| Beam angle (°) | 110 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Colour | White |
| U. G. R | 22 |
| Control gear included | Yes |
| Control gear | 0-10V Dim |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |