



## **MLINE**

Lavov linear system from the family MLINE with a power of  $80\mbox{W}$ and an optics 77 degrees beam angle. CCT 4000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 7200lm and an efficacy of 90 lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

| Item code    | 86.L002.4493.02 Indoor Linear Systems MLINE |  |
|--------------|---|--|
| Product type |   |  |
| Category     |   |  |
| Family       |   |  |
| Subfamily    | MLINE                                       |  |
| Pictograms   | 220 V CRI C € Driver INCL                   |  |
|              | On IP 50000h L80B10                         |  |

| Dimensions              |              |
|-------------------------|--------------|
| Product dimensions (mm) | 75x75X2400mm |

| 2400 |     |
|------|-----|
|      | 280 |

| Product                    |               |
|----------------------------|---------------|
| Real power (W)             | 80            |
| Real luminous flux (Lm)    | 7200          |
| Luminous efficiency (Lm/W) | 90            |
| Beam angle (º)             | 77            |
| Life time (h)              | 50000h L80B10 |
| IP                         | 20            |
| Colour                     | Black         |
| U. G. R                    | <19           |
| Control gear included      | Yes           |
| Control gear               | DALI          |
| Colour temperature (K)     | 4000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |