



**SLIMLINE**

Lavov linear system from the family SLIMLINE with a power of 33W and an optics 70° ↓ / 1140° ↑ degrees beam angle. CCT 3000. CRI 80. Microprismatic diffuser. UGR

<b>Item code</b>	<b>86.L003.1393.02</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>SLIMLINE</b>

**Pictograms**

	220 240 V	CRI 80	CE	Driver INCL.
On Off	1-10V	IP 20	50000h L80B10	

<b>Product</b>	
<b>Real power (W)</b>	<b>33</b>
<b>Real luminous flux (Lm)</b>	<b>4290 (2574lm ↑ +1716lm ↓)</b>
<b>Luminous efficiency (Lm/W)</b>	<b>130</b>
<b>Beam angle (°)</b>	<b>70° ↓ / 1140° ↑</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>20</b>
<b>Colour</b>	<b>Black</b>
<b>U. G. R</b>	<b>&lt;19</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Average life time (h)</b>	<b>50000h L80B10</b>
<b>Colour temperature (K)</b>	<b>3000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>80</b>

**Dimensions**

**Product dimensions (mm)**    **L1200\*W35\*H70mm**

**Scheme**

