



**SLIMLINE**

Lavov linear system from the family SLIMLINE with a power of 33W and an optics 70° ↓ / 1140° ↑ degrees beam angle. CCT 4000. CRI 80. Microprismatic diffuser. UGR

|                     |                        |
|---------------------|------------------------|
| <b>Item code</b>    | <b>86.L003.1493.01</b> |
| <b>Product type</b> | <b>Indoor</b>          |
| <b>Category</b>     | <b>Linear Systems</b>  |
| <b>Family</b>       | <b>SLIMLINE</b>        |
| <b>Subfamily</b>    | <b>SLIMLINE</b>        |

**Pictograms**

|                                   |                                  |
|-----------------------------------|----------------------------------|
| <b>Product</b>                    |                                  |
| <b>Real power (W)</b>             | <b>33</b>                        |
| <b>Real luminous flux (Lm)</b>    | <b>4290 (2574lm ↑ +1716lm ↓)</b> |
| <b>Luminous efficiency (Lm/W)</b> | <b>130</b>                       |
| <b>Beam angle (°)</b>             | <b>70° ↓ / 1140° ↑</b>           |
| <b>Life time (h)</b>              | <b>50000h L80B10</b>             |
| <b>IP</b>                         | <b>20</b>                        |
| <b>Colour</b>                     | <b>White</b>                     |
| <b>U. G. R</b>                    | <b>&lt;19</b>                    |
| <b>Control gear included</b>      | <b>Yes</b>                       |
| <b>Control gear</b>               | <b>DALI</b>                      |
| <b>Light source</b>               | <b>LED</b>                       |
| <b>Type of LED</b>                | <b>SMD</b>                       |
| <b>Average life time (h)</b>      | <b>50000h L80B10</b>             |
| <b>Colour temperature (K)</b>     | <b>4000</b>                      |
| <b>Colour consistency (SDCM)</b>  | <b>SDCM&lt;3</b>                 |
| <b>CRI</b>                        | <b>80</b>                        |

**Dimensions**

**Product dimensions (mm)** L1200\*W35\*H70mm

**Scheme**

