



SLIMLINE

Lavov linear system from the family SLIMLINE with a power of 33W and an optics 70° \downarrow / I140° \uparrow degrees beam angle. CCT 4000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 4290 (2574lm \uparrow +1716lm \downarrow)lm and an efficacy of 130lm/W . Made in Extruded Aluminium and finished in silver grey color. DALI driver.

| Dimensions | |
|-------------------------|-----------------|
| Product dimensions (mm) | L1200*W35*H70mm |
| Scheme | |

| _ | | | |
|--------------|--------------------------------|--|--|
| Item code | 86.L003.1493.03 | | |
| Product type | Indoor Linear Systems SLIMLINE | | |
| Category | | | |
| Family | | | |
| Subfamily | SLIMLINE | | |
| Pictograms | 220 v CRI C € Driver INCL. | | |
| | On | | |

| Product | |
|----------------------------|------------------------|
| Real power (W) | 33 |
| Real luminous flux (Lm) | 4290 (2574lm↑+1716lm↓) |
| Luminous efficiency (Lm/W) | 130 |
| Beam angle (º) | 70°↓ / I140°↑ |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Colour | silver grey |
| U. G. R | <19 |
| Control gear included | Yes |
| Control gear | DALI |
| Light source | LED |
| Type of LED | SMD |
| Average life time (h) | 50000h L80B10 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |