



**SLIMLINE**

Lavov linear system from the family SLIMLINE with a power of 42W and an optics 70° ↓ / 1140° ↑ degrees beam angle. CCT 3000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 5460 (3276lm ↑ +2184lm ↓)lm and an efficacy of 130lm/W . Made in Extruded Aluminium and finished in silver grey color. DALI driver.

<b>Item code</b>	<b>86.L003.2393.03</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>SLIMLINE</b>
<b>Subfamily</b>	<b>SLIMLINE</b>
<b>Pictograms</b>	

**Dimensions**

**Product dimensions (mm)**      **L1500\*W35\*H70mm**

**Scheme**



<b>Product</b>	
<b>Real power (W)</b>	<b>42</b>
<b>Real luminous flux (Lm)</b>	<b>5460 (3276lm ↑ +2184lm ↓)</b>
<b>Luminous efficiency (Lm/W)</b>	<b>130</b>
<b>Beam angle (°)</b>	<b>70° ↓ / 1140° ↑</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>20</b>
<b>Colour</b>	<b>silver grey</b>
<b>U. G. R</b>	<b>19</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Average life time (h)</b>	<b>50000h L80B10</b>
<b>Colour temperature (K)</b>	<b>3000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM3</b>
<b>CRI</b>	<b>80</b>