## SLIMLINE

Lavov linear system from the family SLIMLINE with a power of 42W and an optics 70°↓ / I140°↑ degrees beam angle. CCT 4000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 5460 (3276lm↑+2184lm↓)lm and an efficacy of 130lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

| | |
|---|---|
| **Item code** | **86.L003.2493.02** |
| **Product type** | **Indoor** |
| **Category** | **Linear Systems** |
| **Family** | **SLIMLINE** |
| **Pictograms** |  |

| | |
|---|---|
| **Dimensions** | |
| **Product dimensions (mm)** | **L1500*W35*H70mm** |

**Scheme**




| | |
|---|---|
| **Product** | |
| **Real power (W)** | **42** |
| **Real luminous flux (Lm)** | **5460 (3276lm↑+2184lm↓)** |
| **Luminous efficiency (Lm/W)** | **130** |
| **Beam angle (º)** | **70°↓ / I140°↑** |
| **Life time (h)** | **50000h L80B10** |
| **IP** | **20** |
| **Colour** | **Black** |
| **U. G. R** | **19** |
| **Control gear included** | **Yes** |
| **Control gear** | **DALI** |
| **Light source** | **LED** |
| **Type of LED** | **SMD** |
| **Average life time (h)** | **50000h L80B10** |
| **Colour temperature (K)** | **4000** |
| **Colour consistency (SDCM)** | **SDCM3** |
| **CRI** | **80** |