



IPLINE


Lavov linear system from the family IPLINE with a power of 31W and an optics 107.7 degrees beam angle. CCT 4000. CRI 80. IP65. opal diffuser . UGR22. With a total lumen output of 2936lm and an efficacy of 94.7lm/W . Made in Extruded Aluminium and finished in silver grey color. ON-OFF driver.

| | |
|---------------------|------------------------|
| Item code | 86.L004.1401.03 |
| Product type | Indoor |
| Category | Linear Systems |
| Family | IPLINE |
| Pictograms | |

Dimensions

Product dimensions (mm) L1232mm×W50mm×H80mm

Scheme



| | |
|-----------------------------------|----------------------|
| Product | |
| Real power (W) | 31 |
| Real luminous flux (Lm) | 2936 |
| Luminous efficiency (Lm/W) | 94.7 |
| Beam angle (°) | 107.7 |
| Life time (h) | 50000h L80B10 |
| IP | 65 |
| Colour | silver grey |
| U. G. R | 22 |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Light source | LED |
| Type of LED | SMD |
| Average life time (h) | 50000h L80B10 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |