




Dimensions

Product dimensions (mm) L1841mm×W50mm×H80mm

Scheme



IPLINE

Lavov linear system from the family IPLINE with a power of 46W and an optics 107.7 degrees beam angle. CCT 4000. CRI 80. IP65. opal diffuser . UGR22. With a total lumen output of 4404lm and an efficacy of 95.75lm/W . Made in Extruded Aluminium and finished in White color. ON-OFF driver.

Item code	86.L004.2401.01
Product type	Indoor
Category	Linear Systems
Family	IPLINE
Subfamily	IPLINE
Pictograms	<div><div></div><div>220 240 V</div><div>CRI 80</div><div>CE</div><div>Driver INCL.</div></div> <div><div>On Off</div><div>1-10V</div><div>IP 20</div><div>50000h L80B10</div></div>

Product	
Real power (W)	46
Real luminous flux (Lm)	4404
Luminous efficiency (Lm/W)	95.75
Beam angle (°)	107.7
Life time (h)	50000h L80B10
IP	65
Colour	White
U. G. R	22
Control gear included	Yes
Control gear	ON-OFF
Light source	LED
Type of LED	SMD
Average life time (h)	50000h L80B10
Colour temperature (K)	4000
Colour consistency (SDCM)	SDCM<3
CRI	80