



## **IPLINE**

Lavov linear system from the family IPLINE with a power of 46Wand a beam angle of  $108^{\circ}$ . Finished in Black colour. Dimensions L1841mm $\times$ W50mm $\times$ H80mm.With a total lumen output of 4600lm and a luminous efficacy of 100lm/W. Made in Extruded Aluminium. Driver ON-OFF. CCT 4000K.

| Item code    | 86.L004.2401.02 Indoor Linear Systems IPLINE |  |  |
|--------------|--|--|--|
| Product type |  |  |  |
| Category     |  |  |  |
| Family       |  |  |  |
| Subfamily    | IPLINE                                       |  |  |
| Pictograms   | 220 v CRI 80 C€ Driver INCL.                 |  |  |
|              | On IP 50000h L80B10                          |  |  |

| Dimensions              |                     |  |
|-------------------------|---------------------|--|
| Product dimensions (mm) | L1841mm×W50mm×H80mm |  |

| 85mm(3.23")             | L1841mm |
|-------------------------|---------|
| <sup>32mm</sup> (2.05") | •       |

| Product                    |               |
|----------------------------|---------------|
| Real power (W)             | 46            |
| Real luminous flux (Lm)    | 4600          |
| Luminous efficiency (Lm/W) | 100           |
| Beam angle (º)             | 108           |
| Life time (h)              | 50000h L80B10 |
| IP                         | 65            |
| Colour                     | Black         |
| U. G. R                    | 22            |
| Control gear included      | Yes           |
| Control gear               | ON-OFF        |
| Light source               | LED           |
| Type of LED                | SMD           |
| Average life time (h)      | 50000h L80B10 |
| Colour temperature (K)     | 4000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |

Scheme