



IPLINE

Lavov linear system from the family IPLINE with a power of 61W and an optics 107.7 degrees beam angle. CCT 3000. CRI 80. IP65. opal diffuser . UGR22. With a total lumen output of 5538lm and an efficacy of 90.78lm/W . Made in Extruded Aluminium and finished in silver grey color. ON-OFF driver.

Item code	86.L004.3301.03
Product type	Indoor
Category	Linear Systems
Family	IPLINE
Subfamily	IPLINE
Pictograms	<div><div></div><div>220 240 V</div><div>CRI 80</div><div>CE</div><div>Driver INCL.</div></div> <div><div>On Off</div><div></div><div>1-10V</div><div>IP 20</div><div>50000h L80B10</div></div>

Product	
Real power (W)	61
Real luminous flux (Lm)	5538
Luminous efficiency (Lm/W)	90.78
Beam angle (°)	107.7
Life time (h)	50000h L80B10
IP	65
Colour	silver grey
U. G. R	22
Control gear included	Yes
Control gear	ON-OFF
Light source	LED
Type of LED	SMD
Average life time (h)	50000h L80B10
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	80

Dimensions	
Product dimensions (mm)	L2449mm×W50mm×H80mm

Scheme	
--------	--

