



**IPLINE**


Lavov linear system from the family IPLINE with a power of 61W and an optics 107.7 degrees beam angle. CCT 4000. CRI 80. IP65. opal diffuser . UGR22. With a total lumen output of 5872lm and an efficacy of 96.26lm/W . Made in Extruded Aluminium and finished in silver grey color. DALI driver.

<b>Item code</b>	<b>86.L004.3403.03</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>IPLINE</b>
<b>Pictograms</b>	

**Dimensions**

**Product dimensions (mm)**    **L2449mm×W50mm×H80mm**

**Scheme**



<b>Product</b>	
<b>Real power (W)</b>	<b>61</b>
<b>Real luminous flux (Lm)</b>	<b>5872</b>
<b>Luminous efficiency (Lm/W)</b>	<b>96.26</b>
<b>Beam angle (°)</b>	<b>107.7</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>65</b>
<b>Colour</b>	<b>silver grey</b>
<b>U. G. R</b>	<b>22</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Average life time (h)</b>	<b>50000h L80B10</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>80</b>