



Individual UP&D

Lavov linear luminaire from the family Viewline Individual UP&D with a power of 34W and a beam angle of 65 degrees. CCT 4000K and UGR16.With a real lumen output of 1600+2400lm and a luminous efficiency of 117.64lm/w. Driver ON-OFF. Finished in white color.ON-OFF driver.

Item code	86.L005.1411.01 Indoor Linear Systems Viewline					
Product type						
Category						
Family						
Subfamily	Individual UP&D					
Pictograms	220 v CRI C C Driver					
	On IP 20					

Product			
Real power (W)	34		
Real luminous flux (Lm)	1700+2550		
Luminous efficiency (Lm/W)	125		
Beam angle (º)	65		
Colour	white		
U. G. R	<16		
Chip Brand	philip		
Control gear included	yes		
Control gear	ON-OFF		
Light source	LED		
Type of LED	SMD		
Average life time (h)	50000h L80B10		
Colour temperature (K)	4000		
Colour consistency (SDCM)	<3SDCM		
CRI	>80		
IK	IK02		

Scheme 1200mm

135°	150°	165°	180°	165°	150°	135°
			700			
			600			
、 / /			500			1
			400			
			300			
++			200			1
		\times V		7/		/ / '
45°	30°	15°	00	15°	30°	450