



Individual UP&D

Lavov linear luminaire from the family Viewline Individual UP&D with a power of 34W and a beam angle of 65 degrees. CCT 4000K and UGR16.With a real lumen output of 1600+2400lm and a luminous efficiency of 117.64lm/w. Driver ON-OFF. Finished in black color.ON-OFF driver.

Item code	86.L005.1411.02 Indoor Linear Systems Viewline					
Product type Category						
Subfamily						
Pictograms	220 v CRI C € Driver INCL.					
	On IP 20					

Product	-		
Real power (W)	34		
Real luminous flux (Lm)	1700+2550		
Luminous efficiency (Lm/W)	125		
Beam angle (º)	65		
Colour	black		
U. G. R	<16		
Chip Brand	philip		
Control gear included	yes		
Control gear	ON-OFF		
Light source	LED		
Type of LED	SMD		
Average life time (h)	50000h L80B10		
Colour temperature (K)	4000		
Colour consistency (SDCM)	<3SDCM		
CRI	>80		
IK	IK02		

Scheme 1200mm

135*	150°	165°	180°	165°	150°	1350
			700			
			600			
. / /			500			1
			400			
			\			
.//			300			\ \ _1
			200			
			M			
-						9
				77		
•						
		$\times V$		7)		
450	300	15°	00	15°	30°	45°

