



**Individual UP&D**

Lavov linear luminaire from the family Viewline Individual UP&D with a power of 34W and a beam angle of 65 degrees. CCT 4000K and UGR

<b>Item code</b>	<b>86.L005.1413.01</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>Viewline</b>
<b>Subfamily</b>	<b>Individual UP&amp;D</b>

**Pictograms**

	220 240 V	CRI 80	CE	Driver INCL
On Off		IP 20		

<b>Product</b>	
<b>Real power (W)</b>	<b>34</b>
<b>Real luminous flux (Lm)</b>	<b>1700+2550</b>
<b>Luminous efficiency (Lm/W)</b>	<b>125</b>
<b>Beam angle (°)</b>	<b>65</b>
<b>Colour</b>	<b>white</b>
<b>U. G. R</b>	<b>&lt;16</b>
<b>Chip Brand</b>	<b>philip</b>
<b>Control gear included</b>	<b>yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Average life time (h)</b>	<b>50000h L80B10</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>&lt;3SDCM</b>
<b>CRI</b>	<b>&gt;80</b>
<b>IK</b>	<b>IK02</b>

**Scheme**

