



Wall washer shielded

Lavov linear system from the family Wall washer shielded with a power of 25W and a beam angle of 15° assymmetric. Surface mounted. Finished in Black colour. Dimensions L1000\*W22.5\*H40mm. With a total lumen output of 2250lm and a luminous efficacy of 90lm/W. Made in Extruded Aluminium. Driver not included. CCT 3000K.

Dimensions

Product dimensions (mm) L1000\*W22.5\*H40mm

Scheme



Photometry



Item code	86.L005.2253.02
Product type	Indoor
Category	Linear Systems
Family	Surface washer
Subfamily	Wall washer shielded
Pictograms	<div>CRI 90</div> <div>CE</div> <div>On Off</div> <div>BALTI</div> <div>IP 20</div> <div>50000h L80B10</div>

Product	
Real power (W)	25
Real luminous flux (Lm)	2250
Luminous efficiency (Lm/W)	90
Beam angle (°)	15
Life time (h)	50000h L80B10
Electrical class insulation	Class II
Colour	Black
U. G. R	22
Control gear included	No
Control gear	not included
Power Factor	no includo
Light source	LED
Type of LED	SMD
Average life time (h)	50000h L80B10
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	80