



**Wall washer shielded**

Lavov linear system from the family Wall washer shielded with a power of 25W and a beam angle of 15° assymmetric. Surface mounted. Finished in White colour. Dimensions L1000\*W22.5\*H40mm. With a total lumen output of 2250lm and a luminous efficacy of 90lm/W. Made in Extruded Aluminium. Driver not included. CCT 3000K.


**Dimensions**

Product dimensions (mm) **L1000\*W22.5\*H40mm**

**Scheme**



**Photometry**



<b>Item code</b>	<b>86.L005.2353.01</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>Surface washer</b>
<b>Subfamily</b>	<b>Wall washer shielded</b>
<b>Pictograms</b>	

<b>Product</b>	
<b>Real power (W)</b>	<b>25</b>
<b>Real luminous flux (Lm)</b>	<b>2250</b>
<b>Luminous efficiency (Lm/W)</b>	<b>90</b>
<b>Beam angle (&amp;ordm;)</b>	<b>15</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>Electrical class insulation</b>	<b>Class II</b>
<b>Colour</b>	<b>White</b>
<b>U. G. R</b>	<b>22</b>
<b>Control gear included</b>	<b>No</b>
<b>Control gear</b>	<b>not included</b>
<b>Power Factor</b>	<b>no includo</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Average life time (h)</b>	<b>50000h L80B10</b>
<b>Colour temperature (K)</b>	<b>3000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>80</b>