



Wall washer suspended

Lavov linear system from the family Wall washer suspended with a power of 32 (9,0↑ / 23,0↓)W and a beam angle of ↑ 90° ↓ 15° assymmetric. Suspended mounted 1m cables. Finished in Black colour. Dimensions L1000*W22.5*H80mm. With a total lumen output of 810lm↑ / 2070lm↓ and a luminous efficacy of 90lm/W. Made in Extruded Aluminium. Driver not included. CCT 3000K.

Dimensions

Product dimensions (mm) **L1000*W22.5*H80mm**

Scheme



Photometry



| | |
|---------------------|---|
| Item code | 86.L005.4353.01 |
| Product type | Indoor |
| Category | Linear Systems |
| Family | Surface washer |
| Subfamily | Wall washer suspended |
| Pictograms | <div style="display: flex; gap: 5px;"> <div style="border: 1px solid gray; padding: 2px;">CRI 90</div> <div style="border: 1px solid gray; padding: 2px;">CE</div> <div style="border: 1px solid gray; padding: 2px;">On Off</div> <div style="border: 1px solid gray; padding: 2px;">DALI</div> <div style="border: 1px solid gray; padding: 2px;">IP 20</div> </div> <div style="margin-top: 5px; border: 1px solid gray; padding: 2px; display: inline-block;">50000h L80B10</div> |

| | |
|------------------------------------|--------------------------------|
| Product | |
| Real power (W) | 32 (9,0↑ / 23,0↓) |
| Real luminous flux (Lm) | 810lm↑ / 2070lm↓ |
| Luminous efficiency (Lm/W) | 90 |
| Beam angle (°) | ↑ 90° ↓ 15° assymmetric |
| Life time (h) | 50000h L80B10 |
| Electrical class insulation | Class II |
| Colour | Black |
| U. G. R | 22 |
| Control gear included | No |
| Control gear | not included |
| Power Factor | no includo |
| Light source | LED |
| Type of LED | SMD |
| Average life time (h) | 50000h L80B10 |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM3 |
| CRI | 80 |