




Wall washer suspended


Lavov linear system from the family Wall washer suspended with a power of 32 (9,0↑ / 23,0↓)W and a beam angle of ↑ 90° ↓ 15° assymmetric. Suspended mounted 1m cables. Finished in White colour. Dimensions L1000*W22.5*H80mm. With a total lumen output of 810lm↑ / 2070lm↓ and a luminous efficacy of 90lm/W. Made in Extruded Aluminium. Driver not included. CCT 4000K.

Dimensions	
Product dimensions (mm)	L1000*W22.5*H80mm

Scheme



Photometry



Item code	86.L005.4451.01
Product type	Indoor
Category	Linear Systems
Family	Surface washer
Subfamily	Wall washer suspended
Pictograms	<div style="display: flex; gap: 5px;"> <div style="border: 1px solid black; padding: 2px;">CRI 90</div> <div style="border: 1px solid black; padding: 2px;">CE</div> <div style="border: 1px solid black; padding: 2px;">On Off</div> <div style="border: 1px solid black; padding: 2px;">DALI</div> <div style="border: 1px solid black; padding: 2px;">IP 20</div> </div> <div style="margin-top: 5px; border: 1px solid black; padding: 2px; display: inline-block;">50000h L80B10</div>

Product	
Real power (W)	32 (9,0↑ / 23,0↓)
Real luminous flux (Lm)	810lm↑ / 2070lm↓
Luminous efficiency (Lm/W)	90
Beam angle (º)	↑ 90° ↓ 15° assymmetric
Life time (h)	50000h L80B10
Electrical class insulation	Class II
Colour	White
U. G. R	22
Control gear included	No
Control gear	not included
Power Factor	no includo
Light source	LED
Type of LED	SMD
Average life time (h)	50000h L80B10
Colour temperature (K)	4000
Colour consistency (SDCM)	SDCM<3
CRI	80