



**Wall washer suspended**

Lavov linear system from the family Wall washer suspended with a power of 32 (9,0↑ / 23,0↓)W and a beam angle of ↑ 90° ↓ 15° assymmetric. Suspended mounted 1m cables. Finished in Black colour. Dimensions L1000\*W22.5\*H80mm. With a total lumen output of 810lm↑ / 2070lm↓ and a luminous efficacy of 90lm/W. Made in Extruded Aluminium. Driver not included. CCT 4000K.

**Dimensions**

Product dimensions (mm) **L1000\*W22.5\*H80mm**

**Scheme**



**Photometry**



<b>Item code</b>	<b>86.L005.4451.02</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>Surface washer</b>
<b>Subfamily</b>	<b>Wall washer suspended</b>

**Pictograms**

CRI  
90

CE

On  
Off

DALI

IP  
20

50000h  
L80B10

<b>Product</b>	
<b>Real power (W)</b>	<b>32 (9,0↑ / 23,0↓)</b>
<b>Real luminous flux (Lm)</b>	<b>810lm↑ / 2070lm↓</b>
<b>Luminous efficiency (Lm/W)</b>	<b>90</b>
<b>Beam angle (°)</b>	<b>↑ 90° ↓ 15° assymmetric</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>Electrical class insulation</b>	<b>Class II</b>
<b>Colour</b>	<b>Black</b>
<b>U. G. R</b>	<b>22</b>
<b>Control gear included</b>	<b>No</b>
<b>Control gear</b>	<b>not included</b>
<b>Power Factor</b>	<b>no includo</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Average life time (h)</b>	<b>50000h L80B10</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM3</b>
<b>CRI</b>	<b>80</b>