
**Connect UP&D**

Lavov linear luminaire from the family Viewline Connect UP&D with a power of 34W and a beam angle of 65 degrees. CCT 4000K and UGR


<b>Item code</b>	<b>86.L006.1411.02</b>
------------------	------------------------

<b>Product type</b>	<b>Indoor</b>
---------------------	---------------

<b>Category</b>	<b>Linear Systems</b>
-----------------	-----------------------

<b>Family</b>	<b>Viewline</b>
---------------	-----------------

<b>Subfamily</b>	<b>Connect UP&amp;D</b>
------------------	-------------------------

**Pictograms**

**Product**

<b>Real power (W)</b>	<b>34</b>
-----------------------	-----------

<b>Real luminous flux (Lm)</b>	<b>1700+2550</b>
--------------------------------	------------------

<b>Luminous efficiency (Lm/W)</b>	<b>125</b>
-----------------------------------	------------

<b>Beam angle (°)</b>	<b>65</b>
-----------------------	-----------

<b>Colour</b>	<b>black</b>
---------------	--------------

<b>U. G. R</b>	<b>&lt;16</b>
----------------	---------------

<b>Chip Brand</b>	<b>philip</b>
-------------------	---------------

<b>Control gear included</b>	<b>yes</b>
------------------------------	------------

<b>Control gear</b>	<b>ON-OFF</b>
---------------------	---------------

<b>Light source</b>	<b>LED</b>
---------------------	------------

<b>Type of LED</b>	<b>SMD</b>
--------------------	------------

<b>Average life time (h)</b>	<b>50000h L80B10</b>
------------------------------	----------------------

<b>Colour temperature (K)</b>	<b>4000</b>
-------------------------------	-------------

<b>Colour consistency (SDCM)</b>	<b>&lt;3SDCM</b>
----------------------------------	------------------

<b>CRI</b>	<b>&gt;80</b>
------------	---------------

<b>IK</b>	<b>IK02</b>
-----------	-------------

**Scheme**
