


**Connect UP&D**

Lavov linear luminaire from the family Viewline Connect UP&D with a power of 34W and a beam angle of 65 degrees. CCT 4000K and UGR

|                     |                         |
|---------------------|-------------------------|
| <b>Item code</b>    | <b>86.L006.1413.01</b>  |
| <b>Product type</b> | <b>Indoor</b>           |
| <b>Category</b>     | <b>Linear Systems</b>   |
| <b>Family</b>       | <b>Viewline</b>         |
| <b>Subfamily</b>    | <b>Connect UP&amp;D</b> |

**Pictograms**



**Product**

|                                   |                      |
|-----------------------------------|----------------------|
| <b>Real power (W)</b>             | <b>34</b>            |
| <b>Real luminous flux (Lm)</b>    | <b>1700+2550</b>     |
| <b>Luminous efficiency (Lm/W)</b> | <b>125</b>           |
| <b>Beam angle (°)</b>             | <b>65</b>            |
| <b>Colour</b>                     | <b>white</b>         |
| <b>U. G. R</b>                    | <b>&lt;16</b>        |
| <b>Chip Brand</b>                 | <b>philip</b>        |
| <b>Control gear included</b>      | <b>yes</b>           |
| <b>Control gear</b>               | <b>DALI</b>          |
| <b>Light source</b>               | <b>LED</b>           |
| <b>Type of LED</b>                | <b>SMD</b>           |
| <b>Average life time (h)</b>      | <b>50000h L80B10</b> |
| <b>Colour temperature (K)</b>     | <b>4000</b>          |
| <b>Colour consistency (SDCM)</b>  | <b>&lt;3SDCM</b>     |
| <b>CRI</b>                        | <b>&gt;80</b>        |
| <b>IK</b>                         | <b>IK02</b>          |

**Scheme**

